Leyland Land Rover

88″ Wheelbase, Series III

Leyland Land Rover 88" Wheelbase, Series III. Specifications.

ENGINES

2¼ Petrol

No of cylinders	4
Bore	90.47 mm (3.562 in)
Stroke	88.9 mm (3.5 in)
Capacity	2,286 c.c. (139.5 in³)
Compression ratio	8:1
Max B.H.P. (Din)	52 kw @ 4,000 r.p.m.
Max torque (Din)	159 nm @ 2,000 r.p.m.

2¼ Diesel

No of cylinders	4
Bore	90.47 mm (3.562 in)
Stroke	88.9 mm (3.5 in)
Capacity	2,286 c.c. (139.5 in³)
Compression ratio	23:1
Max B.H.P. (Din)	46 kw @ 4,000 r.p.m.
Max Torque (Din)	137 nm @ 1,800 r.p.m.

LUBRICATION SYSTEM

Pressurised by submerged gear type pump. Gauze pump-intake filter in sump plus external A.C.-Delco, full flow filter.
Sump capacity — 6.25 litres (11 pints) plus 0.85 litres (1½ pints) when new filter fitted.

COOLING SYSTEM

Pressurised with pump, fan and thermostat.

FUEL SYSTEM

2¼ Petrol — Zenith down-draught type carburettor 361.V.E.A.C.-Delco mechanical pump with sediment bowl and priming lever.
2¼ Diesel — C.A.V., D.P.A. distributor type injector pump (self governing) A.C.-Delco high pressure mechanical pump with hand primer. C.A.V. Pintaux injectors.

TRANSMISSION

CLUTCH

Single dry plate 241 mm (9½ in) diameter.
Diaphram spring type. Hydraulic operation.

MAIN GEARBOX

Single helical constant mesh with synchromesh on all forward gears.

TRANSFER GEARBOX

Two speed reduction on main gearbox output. Two/four wheel drive control on transfer box output.

PROPELLER SHAFTS

Open to front and rear axles.

AXLES

Spiral bevel: floating shafts. Ratio: 4.7:1.

OVERALL RATIOS (FINAL DRIVE)

	High transfer	Low transfer
Top	5.40 : 1	11.10 : 1
Third	8.05 : 1	16.50 : 1
Second	12.00 : 1	24.60 : 1
First	19.88 : 1	40.70 : 1
Reverse	21.66 : 1	44.30 : 1

POWER TAKE-OFF POINTS

Central and rear power take-off drives available as optional extras.

CHASSIS

FRAME

Welded fabricated box section side and cross members, black enamel dipped, with channel section galvanised front bumper.

SUSPENSION

Semi-elliptic, underslung road springs. Hydraulic double acting telescopic shock absorbers.

STEERING

Recirculating ball, worm and nut. 432 mm. (17 in) diameter steering wheel. No. of turns lock to lock — 3½.

BRAKES

Footbrake — hydraulic drum brakes. 254 mm (10 in) diameter drums, servo assisted, dual line system.
Hand brake — mechanical, internal expanding drum brake on transfer box output.

WHEELS AND TYRES

Ventilated disc wheels. Size 5.50F x 16in.
Standard tyre and tube size: 7.50 x 16in.
Standard tread: dual purpose (road and cross country).
Special purpose tyres are available as optional extras.

ELECTRICAL SYSTEM

Negative earth, 12 volt.

Battery — Petrol models: 68 A.H.
— Diesel models: 95 A.H.
Alternator —15 A.C.R.
Dual windscreen wipers and electric washers.
Horn — Windtone horn push on steering column stalk.
Heater/demister: fresh air type.

INSTRUMENTS & CONTROLS

Large diameter speedometer with total mileage recorder, incorporating oil pressure, headlamp main beam and cold start warning lights. Fuel and water temperature gauges combined with charging warning light. Panel lights illuminate speedometer, water temperature and fuel gauges.
Petrol models — combined ignition/starter switch operated by key. Toggle switches for head, side and tail lamps. Dip switch operated by steering column control stalk.
Diesel models — Heater/starter/auxiliary switch operated by key. Toggle switch for head, side and tail lamps. Engine stop control. Fuel level warning light. Engine speed hand control. Dip switch operated by steering column control stalk.

LIGHTING

Head lamps. Side lamps. Tail lamps — twin units having double filament stop/tail bulbs. Number plate illumination. Reversing lamps.

BODY

All body panels are non-corrosive light alloy, and all external steel fittings are galvanised.

COLOURS

Body colour — Camino gold
Wheels — Limestone (cream).
Trim — Tan.

OPTIONAL EQUIPMENT

A wide range of optional equipment is available for all models.

IMPORTANT

The specification of this model is correct at April, 1978, but as development is a continuing process, please check details with your dealer.

Leyland Australia is constantly seeking ways to improve the specification, design and production of its vehicles and alterations take place continually. While every effort is made to produce up to date literature, this brochure should not be regarded as an infallible guide to current specifications, nor does it constitute an offer for sale of any particular vehicle.

Dealers and Distributors are not agents of Leyland Australia and have absolutely no authority to bind Leyland Australia by any express or implied undertaking or representation.

DEALER

LAND-ROVER